



**SPECIFICATIONS:**

Current Rating: 1A AC,DC  
 Voltage Rating: 30V AC,DC  
 Temperature Range: -40°C ~ +105°C  
 Contact Resistance: 30mΩ Max.  
 Insulation Resistance: 100MΩ Min.  
 Withstanding Voltage: 200V AC/minute  
 Material: LCP, UL94V-0(Natural)

**Ordering Information & Dimensions**

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	0.80	3.50	12P	8.80	11.50
3P	1.60	4.30	13P	9.60	12.30
4P	2.40	5.10	14P	10.40	13.10
5P	3.20	5.90	15P	11.20	13.90
6P	4.00	6.70	16P	12.00	14.70
7P	4.80	7.50	17P	12.80	15.50
8P	5.60	8.30	18P	13.60	16.30
9P	6.40	9.10	19P	14.40	17.10
10P	7.20	9.90	20P	15.20	17.90
11P	8.00	10.70			



CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	10:1	1 of 1

Title :  
**0.80mm Pitch**  
**Housing**

Draw By:	Approved :
Dlankul Wan	Jack Yin

General Tolerance

x.xx±0.25	PROJECT
x.xxx±0.20	
x.xxxx±0.15	

DRAW NO : **A0801HA-XP**      REV **A0**

A0	NEW RELEASE	2019.06.10
REV	DESCRIPTION	DATE