



SPECIFICATIONS:

Current Rating: 2A AC,DC
 Voltage Rating: 150V AC,DC
 Temperature Range: -40°C ~ +105°C
 Contact Resistance: 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage: 500V AC/minute
 Material: Nylon 66,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)				Circuits	Dimensions(mm)			
	A	B	C	D		A	B	C	D
2P	1.50	6.95	5.95	5.55	8P	10.50	15.95	14.95	14.55
3P	3.00	8.45	7.45	7.05	9P	12.00	17.45	16.45	16.05
4P	4.50	9.95	8.95	8.55	10P	13.50	18.95	17.95	17.55
5P	6.00	11.45	10.45	10.05	11P	15.00	20.45	19.45	19.05
6P	7.50	12.95	11.95	11.55	12P	16.50	21.95	20.95	20.55
7P	9.00	14.45	13.45	13.05					



CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	5:1	1 of 1

Title :

1.50mm PITCH

Draw BY:	Approved :
LIZQ	GONGYB

HOUSING

General Tolerance

A1	Modify drawing	2017.09.20	x.x≤0.25 x.xx≤0.20 x.xxx≤0.15	ANGLE±
A0	NEW RELEEASE	2013.04.17		
REV	DESCRIPTION	DATE		

DRAW NO : A1501HB-XP

REV A0