



SPECIFICATIONS:

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -40°C ~ +105°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1000V AC/minute
 Material: PBT,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2P	2.54	7.12	5.60	13P	30.48	35.06	33.54
3P	5.08	9.66	8.14	14P	33.02	37.60	36.08
4P	7.62	12.20	10.68	15P	35.56	40.14	38.62
5P	10.16	14.74	13.22	16P	38.10	42.68	41.16
6P	12.70	17.28	15.76	17P	40.64	45.22	43.70
7P	15.24	19.82	18.30	18P	43.18	47.74	46.24
8P	17.78	22.36	20.84	19P	45.72	50.30	48.78
9P	20.32	24.90	23.38	20P	48.26	52.84	51.32
10P	22.86	27.44	25.92	21P	50.80	55.36	53.86
11P	25.40	29.98	28.46	22P	53.34	57.90	56.40
12P	27.94	32.52	31.00				



CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	5:1	1 of 1

Title :
2.54mm PITCH
HOUSING

Draw BY:	Approved :
LIZQ	GONGYB

General Tolerance

x.xs±0.25	ANGLE±
x.xx±0.20	
x.xxx±0.15	

DRAW NO : **A2549H-XP** REV **A0**

A0	NEW RELEEASE	2005.05.10
REV	DESCRIPTION	DATE