



SPECIFICATIONS:

Current Rating: 7A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -40°C ~ +105°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-2(Natural)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	3.96	9.06	8P	27.72	32.82
3P	7.92	13.02	9P	31.68	36.78
4P	11.88	16.98	10P	35.64	40.74
5P	15.84	20.94	11P	39.60	44.70
6P	19.80	24.90	12P	43.56	48.66
7P	23.76	28.86			



CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	4:1	1 of 1

Title :
3.96mm PITCH
HOUSING

Draw BY:	Approved :
LIZQ	GONGYB

General Tolerance

x.x≤0.25	ANGLE±
x.xx≤0.20	
x.xxx≤0.15	

DRAW NO : **A3964H-XP-A** REV A0

A0	NEW RELEASE	2005.05.10
REV	DESCRIPTION	DATE