



Ordering Information:

A7501HFA-XP - \*\*\*  
1 2

1.Part No.

2.Material:

(Blank):Nylon 66,UL94V-0/Black

V2:Nylon 66,UL94V-2/Natural

GWT:Nylon 66,UL94V-0,GWT 750 °C/Black

SPECIFICATIONS:

Current Rating: 34A AC,DC

Voltage Rating: 600V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute

Material: Nylon 66,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	7.49	15.98	5P	29.96	38.45
3P	14.98	23.47	6P	37.45	45.94
4P	22.47	30.96	8P	52.43	60.92

**CJTconn**

CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	2:1	1 of 1

Title :

7.49mm Pitch

Draw BY:	Approved :
Tony Su	Jack Yin

Plug Housing

General Tolerance

			x.x±0.25	ANGLE±
A0	NEW RELEASE	2017.07.10	x.xx±0.20	
REV	DESCRIPTION	DATE	x.xxx±0.15	

DRAW NO : A7501HFA-XP

REV  
A0