

Ordering Information:

C3030F-GP-A-H - ^{**}/₂

1.Part No.

2.Finish

(blank): Gold-flash


100µin (2.54µm) MIN.Select Tin

G15:15µin (0.38µm) MIN.Select Gold


100µin (2.54µm) MIN.Select Tin

G30:30µin (0.76µm) MIN.Select Gold

100µin (2.54µm) MIN.Select Tin



SEC:A-A



SEC:B-B

Minimum Area Of
Select Gold Plating
2 Places
(Inside Only)
(Plating G15 and G30 Only)

Note:
Pare Number C3030-T-A-H Is Designed For 18 AWG 1061 Style Wire
Or A 0.073/1.85 Maximum Insulation Outside Diameter

Ordering information & Specifications

Unit:mm

Part No	Wire Range	Insultion O.D.	Material	Finish	Qty/reel
C3030F-TP-A-H	AWG#18 OR 0.75mm ²	1.85mm(max)	Phosphor Bronze	Tin over Nickel	10,000 PCS
C3030F-GP-A-H	AWG#18 OR 0.75mm ²	1.85mm(max)	Phosphor Bronze	Gold over Nickel	10,000 PCS

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	8:1	1 of 1

Title :
3.00mm Pitch

Draw By:	Approved :
Diankui Wan	Jack Yin

Crimp Terminal

REV	DESCRIPTION	DATE
A2	CHANGE THE DRAW NO.	2019.07.25
A1	Change the size	2017.05.18
A0	NEW RELEASE	2017.05.12

General Tolerance	
x.xx±0.25	PROJECT
x.xxx±0.20	
x.xxxx±0.15	

DRAW NO :	C3030F-T-A-H	REV	A2
-----------	--------------	-----	----