


SEC:A-A



SEC:B-B

Ordering information & Specifications

Unit:mm

Part NO.	Wire Range	Insulation O.D.	Material	Finish	Qty/reel
C3030F-TP-D-H	AWG#16-#20	2.20mm(max)	Phosphor Bronze	Tin over Nickel	5,000 PCS
C3030F-GP-D-H	AWG#16-#20	2.20mm(max)	Phosphor Bronze	Gold over Nickel	5,000 PCS
C3030F-TCA-D-H	AWG#16-#20	2.20mm(max)	High conductive copper alloy	Tin over Nickel	5,000 PCS
C3030F-GCA-D-H	AWG#16-#20	2.20mm(max)	High conductive copper alloy	Gold over Nickel	5,000 PCS

REV	DESCRIPTION	DATE
A1	CHANGE THE DRAWING	2021.03.29
A0	NEW RELEASE	2021.02.04

			CHANGJIANG CONNECTORS CO.,LTD.				
			Unit	Scale	Sheet	TITLE	
mm	8:1	1 of 1	<p>3.00mm PITCH CRIMP TERMINAL</p>				
DRWN	CHK'D	APPR				DRAWING NO.	REV
Dengchun Yi	Diankui Wan	Jack Yin				C3030F-T-D-H	A1
General Tolerances		THIRD ANGLE PROJECTION					
x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°							