



**Ordering Information:**

C3962M-GB - \*\*  
1 2

1.Part NO.

2.Finish

(blank): Gold over Nickel,  
1µin (0.025µm) MIN.Select Gold,mating area,  
80~120µin (2.03µm~3.05µm) MIN.Select Tin,other area,  
30~50µin (0.76µm~1.27µm) MIN.Select Nickel,all area.

G15: 15µin (0.38µm) MIN.Select Gold,mating area,  
80~120µin (2.03µm~3.05µm) MIN.Select Tin,other area,  
30~50µin (0.76µm~1.27µm) MIN.Select Nickel,all area.

G30: 30µin (0.76µm) MIN.Select Gold,mating area,  
80~120µin (2.03µm~3.05µm) MIN.Select Tin,other area,  
30~50µin (0.76µm~1.27µm) MIN.Select Nickel,all area.

**Ordering information & Specifications**

Unit:mm

Part NO.	Wire Range	Insultion O.D.	Material	Finish	Qty/reel
C3962M-TB	AWG#22-#26	1.60mm(max)	Brass	Tin over Nickel	8,000 PCS
C3962M-GB	AWG#22-#26	1.60mm(max)	Brass	Gold over Nickel	8,000 PCS

A0	NEW RELEASE	2020.07.14
REV	DESCRIPTION	DATE

**CJTconn** CHANGJIANG CONNECTORS CO.,LTD.

Unit mm	Scale 4:1	Sheet 1 of 1	TITLE <b>3.96mm PITCH CRIMP TERMINAL</b>	
DRWN Dengchun Yi	CHK'D Dlankul Wan	APPR Jack Yin	DRAWING NO. <b>C3962M-T</b>	
General Tolerances x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°		THIRD ANGLE PROJECTION	REV A0	