



Ordering Information:

D0801H-XP - *** - ***
 1 2 3

1.Part No.

2.Material:

(blank) - Nylon 46,UL94V-0(Beige)

66 - Nylon 66,UL94V-0(White)

3.Finish:

(blank) - Tin over Nickel

G - Gold over Nickel

SPECIFICATIONS:

Current rating: 0.5A AC,DC (AWG #32)

Voltage rating: 30V AC,DC

Temperature range: -40°C ~ +105°C

Contact resistance: 20mΩ Max.

Insulation resistance: 100MΩ Min.

Withstanding voltage: 200V AC/minute

Terminal: Phosphor Bronze/Tin-plated

Housing: Nylon 46,UL94V-0(Beige)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	0.80	2.40	10P	7.20	8.80
3P	1.60	3.20	11P	8.00	9.60
4P	2.40	4.00	12P	8.80	10.40
5P	3.20	4.80	13P	9.60	11.20
6P	4.00	5.60	14P	10.40	12.00
7P	4.80	6.40	15P	11.20	12.80
8P	5.60	7.20	16P	12.00	13.60
9P	6.40	8.00			

CJTconn CHANGJIANG CONNECTORS CO.,LTD.

Unit: mm, Scale: 20:1, Sheet: 1 of 1

Draw By: Dlankul Wan, Approved: Jack Yin

General Tolerance

A1: ADD THE INFORMATION, 2019.06.19
 A0: NEW RELEASE, 2005.07.01
 REV: DESCRIPTION, DATE

Title: 0.80mm pitch Insulation Displacement Connector

DRAW NO: D0801H-XP, REV A1