



PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1252 SERIES

PAGE : 1/6

Index

1. Scope
2. Part name & part numbers
3. Construction. dimensions. material & surface finish
4. Ratings & applicable wires
5. Conditions
6. Performance
  - 6.1 Electrical performance
  - 6.2 Mechanical performance
  - 6.3 Environmental performance and others
7. Insertion and Withdrawal Force

			APPROVED	CHECKED	WRITTEN
			BY	BY	BY
			Jack Yin	Diankui Wan	Xi Chen
A0	NEW RELEASE	2023/5/10			
REV.	DESCRIPTION	DATE	DOCUMENT NO: PS-A1252-001		



## PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1252 SERIES

PAGE : 2/6

### 1.SCOPE:

This specification covers the requirements for product performance of 1.25 mm pitch wire to board connector series.

### 2.PART NAME & PART NUMBERS

Part name	Part number
Housing	A1252H A1252H-2
Terminal	A1252-T
Wafer	A1252WV / WR-2 A1252WV / WR-S-2 A1252WV-S-F-2

### 3. CONSTRUCTION. DIMENSIONS . MATERIAL & SURFACE FINISH

Construction and dimensions shall be in accordance with the referenced drawings.  
Material and surface finish shall be as specified below.

Part name		Material	Surface finish
Housing		Nylon 66	UL94V-0
Terminal		Phorphos Bronze	Tin-plated
Wafer	Post	Brass	Tin-plated
	Body	Nylon6T / Nylon 66	UL94V-0

### 4. RATINGS & APPLICABLE WIRES

Item		Standard			
Rated Voltage (Max.)		150V AC DC			Insulation O.D. 1.00mm Max.
Rated Current (Max.) and Applicable Wires	No.of circuits	Wire size (AWG)			
		#26	#28	#30	
	circuits	1.0			
Ambient Temperature Range		-40℃~105℃*			

Note: Do not branch in parallel current which exceeds the rated current

\*: Including terMinal temperature rise

## PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1252 SERIES

PAGE : 3/6

## 5. CONDITIONS:

The conditions shall be in accordance with the referenced data of next table.

Number	Item	Requirement
(1)	Bend up	4°Max.
	Bend down	4°Max.
	Twisting	3°Max.
	Rolling	8°Max.
(2)	Bell mouth (flare)	0.2-0.5 mm
(3)	Cut-off tab length	0.2 mm Max.
(4)	Extruded wire length	0-0.30 mm
(5)	Seam	Seam shall not be opened and no wire allowed out of crimping area
(6)	Wire strip length	1.2-1.7 mm ref.

After crimping, the crimped areas [ (5)、(6) ] should be as follows.

Wire Size (AWG)	Terminal Part Number	Conductor(mm)		Insulation(mm)		Crimp Strength (kgf)
		Crimp Width	Crimp Height	Crimp Width	Crimp Height	
# 26	A1252-T	0.8±0.15	0.70~0.78	1.00(Max)	1.50(max)	1.80(Min.)
# 28			0.35~0.65		1.40(max)	1.00(Min.)
# 30			0.56~0.66		1.25(max)	0.50(Min.)

The crimp width at the conductor part & crimp height at the insulation part is a reference value, so adjust it according to a wire to be used.

## PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1252 SERIES

PAGE : 4/6

## 6. PERFORMANCE

## 6.1 ELECTRICAL PERFORMANCE

Test Description		Procedure	Requirement
6-1-1	Contact Resistance	Mate connectors, measure by dry circuit, 20mV Max. 10mA.	30mΩ Max.
6-1-2	Insulation Resistance	Mate connectors, apply 500V DC between adjacent terminal or ground.	500MΩ Min.
6-1-3	Dielectric Withstanding Voltage	Mate connectors, apply 500V AC (rms) for 1 minute between adjacent terminal or ground.	No Breakdown and Flashover

## 6.2 MECHANICAL PERFORMANCE

Test Description		Procedure	Requirement
6-2-1	Insertion & Withdrawal Force	Insert and withdraw connectors at the speed rate of $25 \pm 3$ mm/minute.	Refer to section 7
6-2-2	Crimping Pull Out Force	Fix the crimped terminal, apply axial pull out force on the wire at the speed rate of $25 \pm 3$ mm/minute.	AWG #26 1.80(Min.)
			AWG #28 1.00(Min.)
			AWG #30 0.50(Min.)
6-2-3	Terminal/Housing Retention Force	Apply axial pull out force at the speed rate of $25 \pm 3$ mm/minute on the terminal assembled in the housing.	0.5kgf Min.
6-2-4	Header Terminal Retention Force	Apply axial push force at the speed rate of $25 \pm 3$ mm/minute.	0.5kgf Min.
6-2-5	Durability	When mated up to 50 cycles by the rate of 10 cycles per minute	Contact Resistance 40mΩ Max.
6-2-7	Vibration	Frequency : 10-55-10 Hz / min Amplitude : 1.5 mm Direction : 1.Axis of up and down 2.Axis of right and left 3.Axis of front and back (MIL-STD-202 , test method 201)	Appearance No Damage
			Contact Resistance 40mΩ Max.
			Discontinuity 1μsec. Max.

## PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1252 SERIES

PAGE : 5/6

## 6.3 ENVIRONMENTAL PERFORMANCE AND OTHERS

Test Description		Procedure		Requirement
6-3-1	Temperature Rise	Carrying rated current load.	Temperature Rise	30°C Max.
6-3-3	Thermal shock	High temperature: $85 \pm 3$ °C Time: 30 minutes Low temperature: $-55 \pm 3$ °C Time: 30 minutes Test round: 25 cycles	Appearance	No Damage
			Contact Resistance	40mΩ Max.
			Insulation Resistance	250MΩ Min.
			Dielectric Withstanding Voltage	Must meet 6-1-3
6-3-4	Humidity	Temperature: $40 \pm 2$ °C Relative Humidity: 90~95% Duration: 240 hours	Appearance	No Damage
			Contact Resistance	40mΩ Max.
			Insulation Resistance	250MΩ Min.
			Dielectric Withstanding Voltage	Must meet 6-1-3
6-3-5	Salt Spray	24 hours exposure to a salt spray from the 5 % solution at $35 \pm 2$ °C.	Appearance	No Damage
			Contact Resistance	40mΩ Max.
6-3-6	Solderability	Soldering Time: 3~5 sec. Solder Temperature: $240 \pm 5$ °C	Solder Wetting	95% of immersed area must show no voids, pin holes
6-3-7	Resistance to Soldering Heat	Soldering Time: 3~5 sec. Solder Temperature: $250 \pm 5$ °C	Appearance	No Damage



**PRODUCT SPECIFICATION**

**PRODUCT SERIES NAME: A1252 SERIES**

PAGE : 6/6

**7. INSERTION AND WITHDRAWAL FORCE**

**PREPLATED TIN**

unit: kgf

Number of Circuits	Insertion (Max.)	Withdrawal (Min.)	
	1 th	1 th	50 th
Single	1.00	0.15	0.10
2P	1.50	0.20	0.15
3P	2.00	0.25	0.20
4P	2.50	0.30	0.25
5P	3.00	0.40	0.35
6P	3.50	0.60	0.50
7P	4.00	0.80	0.70
8P	4.50	1.00	0.90
9P	5.00	1.20	1.10
10P	5.50	1.40	1.30
11P	6.00	1.60	1.50
12P	6.50	1.80	1.60
13P	7.00	2.00	1.80
14P	7.50	2.20	2.00
15P	8.00	2.40	2.20

Requirement : (Dual Row)

Number of Circuits	Insertion (Max.)	Withdrawal (Min.)	
	1 th	1 th	50 th
2x5P	4.00	0.50	0.60
2x10P	6.00	1.00	0.90
2x15P	8.00	1.50	1.40
2x20P	10.00	2.00	1.90