



PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A3961 SERIES

PAGE : 1/5

Index

1. Scope
2. Part name & part numbers
3. Construction. dimensions. material & surface finish
4. Ratings & applicable wires
5. Conditions
6. Performance
 - 6.1 Electrical performance
 - 6.2 Mechanical performance
 - 6.3 Environmental performance and others

				APPROVED	CHECKED	WRITTEN
				BY	BY	BY
				Jack Yin	Diankui Wan	Wenmin Luo
A1	MODIFY THE INFORMATION	2020.12.12	Diankui Wan			
A0	NEW RELEASE	2009.06.24	Zhouchaohui			
REV.	DESCRIPTION	DATE	NAME	DOCUMENT NO: PS-A3961-002		

PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A3961 SERIES

PAGE : 2/5

1.SCOPE:

This specification covers the requirements for product performance of 3.96mm pitch wire to board connector series.

2.PART NAME & PART NUMBERS

Part Name	Part Number
Housing	A3961H
Terminal	A3961-T
Wafer	A3961WV/WVA/WVB/WVC/WVE
	A3961WR/WRA/WRB/WRC/WRE

3. CONSTRUCTION. DIMENSIONS . MATERIAL & SURFACE FINISH

Construction and dimensions shall be in accordance with the referenced drawings.

Material and surface finish shall be as specified below.

Part Name	Material		Surface finish
Housing	Nylon 66		UL94V-2/UL94V-0
Terminal	Brass/Phosphor Bronze		Tin over Nickel/Gold over Nickel
Wafer	Body	Nylon 66/PBT/LCP	UL94V-0
	Pin	Brass	Tin over Nickel/Gold over Nickel

4. RATINGS & APPLICABLE WIRES

Item	Standard		
Rated Voltage (Max.)	250V AC DC		Insulation O.D. 2.80mm (Max.)
Rated Current (Max.) and Applicable Wires	AWG #18	7A AC DC (W-B 2-circuit)	
	AWG #20	5A AC DC (W-B 2-circuit)	
	AWG #22	4A AC DC (W-B 2-circuit)	
	AWG #24	3A AC DC (W-B 2-circuit)	
Ambient Temperature Range	-40℃~105℃*		

*: Including terminal temperature rise

PRODUCT SPECIFICATION
PRODUCT SERIES NAME: A3961 SERIES

PAGE : 3/5

5. CONDITIONS:

Number	Item	Requirement
①	Bend up	4°Max.
	Bend down	4°Max.
	Twisting	3°Max.
	Rolling	8°Max.
②	Bell mouth (flare)	0.2-0.5 mm
③	Cut-off tab length	0.2 mm Max.
④	Extruded wire length	0-1.5 mm
⑤	Seam	Seam shall not be opened and no wire
⑥	Wire strip length	1.2-1.7 mm ref.
⑦	Lance height	0.3 mm ref.

After crimping, the crimped areas [⑤、⑥] should be as follows.

Wire Size (AWG)	Terminal Part Number	Conductor(mm)		Insulation(mm)		Crimp Strength (kgf)
		Crimp Width	Crimp Height	Crimp Width	Crimp Height	
#18	A3961-T	1.80±0.05	1.30-1.40	2.80 (max)	2.10(max)	9.0(min)
#20			1.20~130		2.00(max)	5.9(min)
#22			1.10~1.20		1.80(max)	4.0(min)
#24			1.00~1.10		1.60(max)	3.0(min)

Note: no distorted after terminal crimped.

6. PERFORMANCE
6.1 ELECTRICAL PERFORMANCE

Test Description		Procedure	Requirement
6-1-1	Contact Resistance	Mate connectors, measure by dry circuit, 20mV Max. 10mA. (Based upon JIS C5402 5.4)	10mΩ Max.
6-1-2	Insulation Resistance	Mate connectors, apply 500V DC between adjacent terminal or ground. (Based upon JIS C5402 5.2/MIL-STD-202 Method 302 Cond. B)	1000MΩ Min.
6-1-3	Dielectric Withstanding Voltage	Mate connectors, apply 1500V AC (rms) for 1 minute between adjacent terminal or ground. (Based upon JIS C5402 5.1/MIL-STD-202 Method	No Breakdown
6-1-4	Contact Resistance on Crimped Portion	Crimp the applicable wire on to the terminal, measure by dry circuit, 20mV Max., 10mA.	5mΩ Max.

PRODUCT SPECIFICATION
PRODUCT SERIES NAME: A3961 SERIES

PAGE : 4/5

6.2 MECHANICAL PERFORMANCE

Test Description		Procedure		Requirement
6-2-1	Insertion & Withdrawal Force	Insert and withdraw connectors at the speed rate of 25 ± 3 mm/minute.		1.00kgf per circuit MAX mate force & 0.30kgf per circuit MIN unmate force
6-2-2	Crimping Pull Out Force	Fix the crimped terminal, apply axial pull out force on the wire at the speed rate of 25 ± 3 mm/minute. (Based upon JIS C5402 6.8)	AWG #16	10.0kgf Min.
			AWG #18	9.0kgf Min.
			AWG #20	5.9kgf Min.
			AWG #22	3.9kgf Min.
6-2-3	Terminal/Housing Retention Force	Apply axial pull out force at the speed rate of 25 ± 3 mm/minute on the terminal assembled in the		2.5kgf Min.
6-2-4	Post Retention Force	Apply axial push force at the speed rate of 25 ± 3 mm/minute.		2.5kgf Min.
6-2-5	Durability	When mated up to 30 cycles repeatedly	Contact Resistance	20mΩ Max.
6-2-6	Vibration	Amplitude: 1.52mm P-P Sweep time: 10-55-10 Hz/min Duration: 2 hours in each X.Y.Z. axes (Based upon MIL-STD-202 Method 201A)	Appearance	No Damage
			Contact Resistance	20mΩ Max.
			Discontinuity	1μsec. Max.
6-2-7	Physical Shock	490m/s ² {50G}, 3 strokes in each X.Y.Z. axes. (Based upon JIS C0041/MIL-STD-202 Method 213B Cond. A)	Appearance	No Damage
			Contact Resistance	20mΩ Max.
			Discontinuity	1μsec. Max.

PRODUCT SPECIFICATION
PRODUCT SERIES NAME: A3961 SERIES

PAGE : 5/5

6.3 ENVIRONMENTAL PERFORMANCE AND OTHERS

Test Description		Procedure		Requirement
6-3-1	Temperature Rise	Carrying rated current load. (Based upon UL 498)	Temperature Rise	30°C Max.
6-3-2	Heat Resistance	105 ± 2°C, 96 hours (Based upon JIS C0021/MIL-STD-202 Method 108A Cond. A)	Appearance	No Damage
			Contact Resistance	20mΩ Max.
6-3-3	Cold Resistance	-40 ± 3°C, 96 hours (Based upon JIS C0020)	Appearance	No Damage
			Contact Resistance	20mΩ Max.
6-3-4	Humidity	Temperature: 40 ± 2°C Relative Humidity: 90 ~ 95% Duration: 96 hours (Based upon JIS C0022/MIL-STD-202 Method 103B Cond. B)	Appearance	No Damage
			Contact Resistance	20mΩ Max.
			Insulation Resistance	100MΩ Min.
			Dielectric Withstandin	Must meet 6-1-3
6-3-5	Temperature Cycling	5 cycles of: a) - 55°C 30 minutes b) +85°C 30 minutes (Based upon JIS C0025)	Appearance	No Damage
			Contact Resistance	20mΩ Max.
6-3-6	Salt Spray	24 hours exposure to a salt spray from the 5 % solution at 35 ± 2°C. (Based upon JIS C0023/MIL-STD-202 Method 101A Cond. A)	Appearance	No Damage
			Contact Resistance	20mΩ Max.
6-3-7	SO ₂ Gas	24 hours exposure to 50 ± 5ppm. SO ₂ gas at 40 ± 2°C.	Appearance	No Damage
			Contact Resistance	20mΩ Max.
6-3-8	NH ₃ Gas	40 minutes exposure to NH ₃ gas evaporating from 28% Ammonia solution.	Appearance	No Damage
			Contact Resistance	20mΩ Max.
6-3-9	Solderability	Soldering Time: 3~5 sec. Solder Temperature: 240 ± 5°C	Solder Wetting	Solder coverage: 95% MIN
6-3-10	Resistance to Soldering Heat	<u>Normal materials</u> Soldering Time: 3~5 sec. Solder Temperature: 250 ± 5°C <u>High temperature resistant materials</u> Soldering Time: 3~5 sec. Solder Temperature: 260 ± 5°C (Based upon EIA 364-29)	Appearance	No Damage