



PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A7501 HFA HMA SERIES

PAGE : 1/5

Index

1. Scope
2. Part name & part numbers
3. Construction. dimensions. material & surface finish
4. Ratings & applicable wires
5. Performance
 - 5.1 Electrical performance
 - 5.2 Mechanical performance
 - 5.3 Environmental performance and others

			APPROVED	CHECKED	WRITTEN
			BY	BY	BY
			<i>Jack Yin</i>	<i>Lailin</i>	<i>Diankui Wan</i>
A0	NEW RELEASE	2017.10.08			
REV.	DESCRIPTION	DATE	DOCUMENT NO: PS-7501-002		

PRODUCT SPECIFICATION
PRODUCT SERIES NAME: A7501 HFA HMA SERIES

PAGE : 2/5

1.SCOPE:

This specification covers the requirements for product performance of 7.50mm pitch wire to wire connector series.

2.PART NAME & PART NUMBERS

Part name	Part number
Housing	A7501HFA A7501HMA
Terminal	A7501AF-T A7501AM-T

3. CONSTRUCTION. DIMENSIONS . MATERIAL & SURFACE FINISH

Construction and dimensions shall be in accordance with the referenced drawings.

Material and surface finish shall be as specified below.

Part name	Material	Surface finish
Housing	Nylon 66	UL94V-0
Terminal	Brass/Copper Alloy	in over Nickel/Silver over Nickel/Unplate

4. RATINGS & APPLICABLE WIRES

Item	Standard		
Rated Voltage (max.)	600V AC DC		Insulation O.D. 4.57mm (max.)
Rated Current (max.) and Applicable Wires	AWG #10	34A AC DC(W-W,2Circuits)	
	AWG #12	28A AC DC(W-W,2Circuits)	
	AWG #10	32A AC DC(W-W,4Circuits)	
	AWG #12	26A AC DC(W-W,4Circuits)	
	AWG #10	32A AC DC(W-W,6Circuits)	
	AWG #12	26A AC DC(W-W,6Circuits)	
	AWG #10	32A AC DC(W-B,2Circuits)	
	AWG #12	28A AC DC(W-B,2Circuits)	
	AWG #10	30A AC DC(W-B,3Circuits)	
	AWG #12	26A AC DC(W-B,3Circuits)	
	AWG #10	28A AC DC(W-B,6Circuits)	
	AWG #12	26A AC DC(W-B,6Circuits)	
Ambient Temperature Range	-40℃~105℃*		

*: Including terminal temperature rise



PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A7501 HFA HMA SERIES

PAGE : 3/5

5. PERFORMANCE

5.1 ELECTRICAL PERFORMANCE

Test Description		Procedure	Requirement
5-1-1	Contact Resistance	Mate connectors, measure by dry circuit, 20mV max. 10mA. (Based upon JIS C5402 5.4)	10mΩ max.
5-1-2	Insulation Resistance	Mate connectors, apply 500V DC between adjacent terminal or ground. (Based upon JIS C5402 5.2/MIL-STD-202 Method 302 Cond. B)	1000MΩ min.
5-1-3	Dielectric Withstanding Voltage	Mate connectors, apply 1500V AC (rms) for 1 minute between adjacent terminal or ground. (Based upon JIS C5402 5.1/MIL-STD-202 Method 301)	No Breakdown
5-1-4	Contact Resistance on Crimped Portion	Crimp the applicable wire on to the terminal, measure by dry circuit, 20mV max., 10mA.	5mΩ max.

PRODUCT SPECIFICATION
PRODUCT SERIES NAME: A7501 HFA HMA SERIES

PAGE : 4/5

5.2 MECHANICAL PERFORMANCE

Test Description		Procedure		Requirement
5-2-1	Insertion & Withdrawal Force	Insert and withdraw connectors at the speed rate of 25 ± 3 mm/minute.		Insertion: 1.81kgf max. per circuit Withdrawal: 0.45kgf min.
5-2-2	Crimping Pull Out Force	Fix the crimped terminal, apply axial pull out force on the wire at the speed rate of 25 ± 3 mm/minute. (Based upon JIS C5402 6.8)	AWG #10	36.3kgf min.
			AWG #12	31.7kgf min.
5-2-3	Terminal Insertion Force	Insert the crimped terminal into the housing at a constant speed of 25 ± 3 mm per minute.		1.1kgf max.
5-2-4	Terminal/Housing Retention Force	Apply axial pull out force at the speed rate of 25 ± 3 mm/minute on the terminal assembled in the housing.		6.8kgf min.
5-2-5	Durability	When mated up to 50 cycles repeatedly by the rate of 10 cycles per minute.	Contact Resistance	20mΩ max.
5-2-6	Vibration	Amplitude: 1.5mm P-P Sweep time: 10-55-10 Hz in 1 minute Duration: 2 hours in each X.Y.Z. axes (Based upon MIL-STD-202 Method 201A)	Appearance	No Damage
			Contact Resistance	20mΩ max.
			Discontinuity	1μsec. max.
5-2-7	Physical Shock	490m/s ² {50G}, 3 strokes in each X.Y.Z. axes. (Based upon JIS C0041/MIL-STD-202 Method 213B Cond. A)	Appearance	No Damage
			Contact Resistance	20mΩ max.
			Discontinuity	1μsec. max.

PRODUCT SPECIFICATION
PRODUCT SERIES NAME: A7501 HFA HMA SERIES

PAGE : 5/5

5.3 ENVIRONMENTAL PERFORMANCE AND OTHERS

Test Description		Procedure		Requirement
5-3-1	Temperature Rise	Carrying rated current load. (Based upon UL 498)	Temperature Rise	30°C max.
5-3-2	Heat Resistance	105 ± 2°C, 96 hours (Based upon JIS C0021/MIL-STD-202 Method 108A Cond. A)	Appearance	No Damage
			Contact Resistance	20mΩ max.
5-3-3	Cold Resistance	-40 ± 3°C, 96 hours (Based upon JIS C0020)	Appearance	No Damage
			Contact Resistance	20mΩ max.
5-3-4	Humidity	Temperature: 60 ± 2°C Relative Humidity: 90 ~ 95% Duration: 96 hours (Based upon JIS C0022/MIL-STD-202 Method 103B Cond. B)	Appearance	No Damage
			Contact Resistance	20mΩ max.
			Insulation Resistance	100MΩ min.
			Dielectric Withstanding	Must meet 5-1-3
5-3-5	Temperature Cycling	5 cycles of: a) -55 °C 30 minutes b) +85 °C 30 minutes (Based upon JIS C0025)	Appearance	No Damage
			Contact Resistance	20mΩ max.
5-3-6	Salt Spray	24 ± 4 hours exposure to a salt spray from the 5 ± 1% solution at 35 ± 2°C. (Based upon JIS C0023/MIL-STD-202 Method 101A Cond. A)	Appearance	No Damage
			Contact Resistance	20mΩ max.
5-3-7	SO ₂ Gas	24 hours exposure to 50 ± 5ppm. SO ₂ gas at 40 ± 2°C.	Appearance	No Damage
			Contact Resistance	20mΩ max.
5-3-8	NH ₃ Gas	40 minutes exposure to NH ₃ gas evaporating from 28% Ammonia solution.	Appearance	No Damage
			Contact Resistance	20mΩ max.
5-3-9	Solderability	Soldering Time: 3 ± 0.5 sec. Solder Temperature: 235± 5°C	Solder Wetting	95% of immersed area must show no voids, pin
5-3-10	Resistance to soldering heat	Soldering Time: 3 ± 0.5 sec. Solder Temperature: 260± 5°C	Appearance	No Damage