



**Ordering Information:**

A1501WR-S-F-XP - \*  
1 2

- Part NO.
- Pin Finish:  
(blank): Tin over Nickel  
G: Gold over Nickel

**SPECIFICATIONS:**

Current Rating: 2A AC, DC (AWG #24)  
Voltage Rating: 100V AC, DC  
Temperature Range: -40°C ~ +105°C  
Contact Resistance: 30mΩ Max.  
Insulation Resistance: 500MΩ Min.  
Withstanding Voltage: 500V AC/minute  
Pin Material: Brass  
Wafer: Nylon 9T, UL94V-0(Beige)

**Ordering Information & Dimensions**

Part NO.	Dimensions(mm)	
	A	B
A1501WR-S-F-2P	1.50	4.50
A1501WR-S-F-3P	3.00	6.00
A1501WR-S-F-4P	4.50	7.50
A1501WR-S-F-5P	6.00	9.00
A1501WR-S-F-6P	7.50	10.50
A1501WR-S-F-7P	9.00	12.00
A1501WR-S-F-8P	10.50	13.50
A1501WR-S-F-9P	12.00	15.00
A1501WR-S-F-10P	13.50	16.50
A1501WR-S-F-11P	15.00	18.00
A1501WR-S-F-12P	16.50	19.50
A1501WR-S-F-13P	18.00	21.00

**CJTconn** CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	5:1	1 of 1
DRWN	CHK'D	APPR
Haisen Li	Diankui Wan	Jack Yin

TITLE  
**1.50mm PITCH  
90° WAFER - SMD TYPE**

A1	CHANGE THE DRAWING	2021.12.15
A0	NEW RELEASE	2017.08.19
REV	DESCRIPTION	DATE

General Tolerances  
x.xx±0.25  
x.xxx±0.20  
x.xxxx±0.15  
ANGLES ±1°

THIRD ANGLE PROJECTION

DRAWING NO.	REV
A1501WR-S-F-XP	A1