



ASSEMBLY LAYOUT
Mated with A2005HI-2xXP

SPECIFICATIONS:

Current Rating: 2A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 20mΩ Max.
Insulation Resistance: 1000MΩ Min.
Withstanding Voltage: 500V AC/minute
Material: PBT,UL94V-0(Black)

Ordering Information & Dimensions

Part No.	Dimensions (mm)	Part No.	Dimensions (mm)
	B		B
A2005HJ-2x5P	15.95	A2005HJ-2x16P	37.95
A2005HJ-2x6P	17.95	A2005HJ-2x17P	39.95
A2005HJ-2x7P	19.95	A2005HJ-2x18P	41.95
A2005HJ-2x8P	21.95	A2005HJ-2x19P	43.95
A2005HJ-2x9P	23.95	A2005HJ-2x20P	45.95
A2005HJ-2x10P	25.95	A2005HJ-2x21P	47.95
A2005HJ-2x11P	27.95	A2005HJ-2x22P	49.95
A2005HJ-2x12P	29.95	A2005HJ-2x23P	51.95
A2005HJ-2x13P	31.95	A2005HJ-2x24P	53.95
A2005HJ-2x14P	33.95	A2005HJ-2x25P	55.95
A2005HJ-2x15P	35.95		

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit		Scale		Sheet		Title : 2.00mm PITCH	
mm		1.5:1		1 of 1			
Draw By:			Approved :			IDC Socket	
Diankui Wan			Jack Yin				
General Tolerance						DRAW NO : A2005HJ-2xXP	
x.x±0.25 x.xx±0.20 x.xxx±0.15		PROJECT 					
4						REV A0	

x.x±0.25
x.xx±0.20
x.xxx±0.15

PROJECT