








P.C.B LAYOUT
TOLERANCE:±0.05



Ordering Information:
A2005WVCB-N-F-XP - ***
1 2

- 1.Part NO.
2.Pin Finish:
(blank): Gold over Nickel
G15: Gold over Nickel(Au:15u",Mating Area)

SPECIFICATIONS:

Current Rating: 3A AC,DC (MAX)
Voltage Rating: 250V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 10mΩ Max.
Insulation Resistance: 1000MΩ Min.
Withstanding Voltage: 800V AC/minute
Pin Material: Brass
Material: Nylon 4T,UL94V-0(Black)

Ordering Information & Dimensions

Part NO.	Dimensions(mm)		
	A	B	C
A2005WVCB-N-F-4P	6.00	13.10	11.10
A2005WVCB-N-F-5P	8.00	15.10	13.10
A2005WVCB-N-F-6P	10.00	17.10	15.10
A2005WVCB-N-F-7P	12.00	19.10	17.10
A2005WVCB-N-F-8P	14.00	21.10	19.10
A2005WVCB-N-F-9P	16.00	23.10	21.10
A2005WVCB-N-F-10P	18.00	25.10	23.10

CJTconn CHANGJIANG CONNECTORS CO.,LTD.			
Unit	Scale	Sheet	TITLE
mm	3:1	1 of 1	2.00mm PITCH 180° SINGLE ROW BOX HEADER
DRWN	CHK'D	APPR	
Dengchun Yi	Dlankul Wan	Jack Yin	
General Tolerances		THIRD ANGLE PROJECTION	
x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°			DRAWING NO.
			A2005WVCB-N-F-XP
			REV A0