



Ordering Information:

A2005WVE-F-2xXP - **
1 2

1.Part NO.

2.Finish:

(Blank): Gold over Nickel (Au:1u")

G30: Gold over Nickel (Au:30u", Mating Area)

SPECIFICATIONS:

Current Rating: 3A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 20mΩ Max.

Insulation Resistance: 1000MΩ Min.

Withstanding Voltage: 500V AC/minute

Pin Material: Brass

Housing Material: Nylon 46,UL94V-0(Black)

Ordering Information & Dimensions

| Part NO. | Dimensions(mm) | |
|-----------------|----------------|-------|
| | A | B |
| A2005WVE-F-2x3P | 4.00 | 9.80 |
| A2005WVE-F-2x4P | 6.00 | 11.80 |

CJTconn CHANGJIANG CONNECTORS CO.,LTD.

| | | |
|-------------|-------------|----------|
| Unit | Scale | Sheet |
| mm | 4:1 | 1 of 1 |
| DRWN | CHK'D | APPR |
| Dengchun Yi | Diankui Wan | Jack Yin |

TITLE
**2.00mm PITCH
DUAL ROW DIP WAFER**

| | |
|--------------------|------------------------|
| General Tolerances | THIRD ANGLE PROJECTION |
| x.xx±0.25 | |
| x.xxx±0.20 | |
| x.xxxx±0.15 | |
| ANGLES ±1° | |

| | |
|-----------------|-----|
| DRAWING NO. | REV |
| A2005WVE-F-2xXP | A0 |

| | | |
|-----|-------------|------------|
| A0 | NEW RELEASE | 2020.06.24 |
| REV | DESCRIPTION | DATE |