




Ordering Information:

A2006WRU-F-2xXP - ^{***}1 - ^{***}2 - ^{*}3 - ^{*}4

1.Part NO.

2.Size L

(Blank): 3.00mm

L18: 1.80mm

3.Color

(Blank): Natural

BK: Black

CB: Cobalt Blue

DP: Dark Durple

IV: Ivory

DPK: Dark pink

LE: Light blue

TR: Tomato red

4.Finish

(Blank): Tin over Nickel

G: Gold over Nickel

BL: Blue

DO: Dark Orange

DH: Dark Gray

OR: Orange

MG: Moss green

LY: Lemon yellow

SPECIFICATIONS:

Current Rating: 3A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 10mΩ Max.

Insulation Resistance: 1000MΩ Min.





Withstanding Voltage: 800V AC/minute

Pin Material: Brass


Material: PA4T,UL94V-0,Halogen Free

Ordering Information & Dimensions


Part NO.	Dimensions(mm)	
	A	B
A2006WRU-F-2x4P	6.00	10.00
A2006WRU-F-2x5P	8.00	12.00
A2006WRU-F-2x6P	10.00	14.00
A2006WRU-F-2x7P	12.00	16.00
A2006WRU-F-2x8P	14.00	18.00
A2006WRU-F-2x9P	16.00	20.00
A2006WRU-F-2x10P	18.00	22.00
A2006WRU-F-2x11P	20.00	24.00
A2006WRU-F-2x12P	22.00	26.00
A2006WRU-F-2x13P	24.00	28.00
A2006WRU-F-2x14P	26.00	30.00
A2006WRU-F-2x15P	28.00	32.00
A2006WRU-F-2x16P	30.00	34.00
A2006WRU-F-2x17P	32.00	36.00
A2006WRU-F-2x18P	34.00	38.00
A2006WRU-F-2x19P	36.00	40.00
A2006WRU-F-2x20P	38.00	42.00




2x4P~2x7P Without Guideway
2x8P~2x20P With Guideway



2x4P~2x5P



2x6P~2x9P



2x10P~2x20P

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet	TITLE	
mm	2.5:1	1 of 1	2.00mm PITCH RIGHT ANGLE DUAL ROW WAFER	
DRAWN	CHK'D	APPR		
Haisen Li	Diankui Wan	Jack Yin	DRAWING NO.	
General Tolerances			THIRD ANGLE PROJECTION	
x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°			A2006WRU-F-2xXP	
REV	DESCRIPTION	DATE	REV A3	

A3	CHANGE THE INFORMATION	2022.12.26
A2	CHANGE THE INFORMATION	2021.02.01
A1	CHANGE THE DRAWING	2017.08.11
A0	NEW RELEASE	2016.07.20
REV	DESCRIPTION	DATE