








Ordering Information:

A2549WRI-XP - *** - ***
1 2 3

1.Part NO.

2.Color:

(Blank): Ivory

BK: Black

3.Finish:

(Blank): Gold over Nickel

G10: Gold over Nickel(Au:10µin[0.25µm] Min,Mating Area)

G15: Gold over Nickel(Au:15µin[0.38µm] Min,Mating Area)

G30: Gold over Nickel(Au:30µin[0.76µm] Min,Mating Area)

MT: Matte Tin over Nickel

SPECIFICATIONS:

Current Rating: 3A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 20mΩ Max.

Insulation Resistance: 1000MΩ Min.

Withstanding Voltage: 1000V AC/minute

Pin Material: Brass

Material: LCP,UL94V-0

Ordering Information & Dimensions

Part NO.	Dimensions(mm)		Part NO.	Dimensions(mm)	
	A	B		A	B
2P	2.54	6.60	14P	33.02	37.08
3P	5.08	9.14	15P	35.56	39.62
4P	7.62	11.68	16P	38.10	42.16
5P	10.16	14.22	17P	40.64	44.70
6P	12.70	16.76	18P	43.18	47.24
7P	15.24	19.30	19P	45.72	49.78
8P	17.78	21.84	20P	48.26	52.32
9P	20.32	24.38	21P	50.80	54.86
10P	22.86	26.92	22P	53.34	57.40
11P	25.40	29.46	23P	55.88	59.94
12P	27.94	32.00	24P	58.42	62.48
13P	30.48	34.54	25P	60.96	65.02

CJTconn CHANGJIANG CONNECTORS CO.,LTD.			
Unit	Scale	Sheet	TITLE 2.54mm PITCH RIGHT-ANGLE SINGLE ROW WAFER
mm	3:1	1 of 1	
DRAWN	CHK'D	APPR'D	
Haisen Li	Diankui Wan	Jack Yin	DRAWING NO. A2549WRI-XP
General Tolerances		THIRD ANGLE PROJECTION	
x.x±0.25 x.xx±0.20 x.xxx±0.15 ANGLES ±1°			
			REV A0