

Ordering Information:

A3963H-XP - $\frac{**}{2}$ $\frac{***}{3}$

1.Part No.

2.Material:

(Blank): Nylon 66,UL94V-0(White)

GWT: Nylon 66,UL94V-0(Beige),

IEC 60335-1,5th Edition

Glow Wire Capable.

3.Color:

(Blank): see section 2 Material

BK: Black BR: Brown

RD: Red BL:Blue

SPECIFICATIONS:

Current Rating: 10A AC,DC(AWG #16)

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute

Ordering Information & Dimensions

Part NO.	Dimensions(mm)	
	A	B
A3963H-2P	3.96	8.02
A3963H-3P	7.92	11.98
A3963H-4P	11.88	15.94
A3963H-5P	15.84	19.90
A3963H-6P	19.80	23.86
A3963H-7P	23.76	27.82
A3963H-8P	27.72	31.78
A3963H-9P	31.68	35.74
A3963H-10P	35.64	39.70
A3963H-11P	39.60	43.66
A3963H-12P	43.56	47.62
A3963H-13P	47.52	51.58
A3963H-14P	51.48	55.54
A3963H-15P	55.44	59.50

CJTconn				CHANGJIANG CONNECTORS CO.,LTD.	
Unit	Scale	Sheet	TITLE		
mm	3:1	1 of 1	3.96mm PITCH HOUSING		
DRWN	CHKD	APPR			
Wenmin Luo	Diankui Wan	Jack Yin			
General Tolerances		THIRD ANGLE PROJECTION		DRAWING NO. A3963H-XP	
x.xx±0.25					
x.xxx±0.20					
x.xxxx±0.15					
ANGLES ±1°				REV A2	

A2	CHANGE THE DRAWING	2021.11.03
A1	CHANGE THE DRAWING	2021.03.11
A0	NEW RELEASE	2005.05.10
REV	DESCRIPTION	DATE

