







SPECIFICATIONS:

Current Rating: 2A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 800V AC/minute
Material: Nylon 66,UL94V-0(White)

Ordering Information & Dimensions

Part NO.	Dimensions(mm)	
	A	B
B2011H-2P	2.00	5.20
B2011H-3P	4.00	7.20
B2011H-4P	6.00	9.20
B2011H-5P	8.00	11.20
B2011H-6P	10.00	13.20
B2011H-7P	12.00	15.20
B2011H-8P	14.00	17.20
B2011H-9P	16.00	19.20
B2011H-10P	18.00	21.20
B2011H-11P	20.00	23.20
B2011H-12P	22.00	25.20
B2011H-13P	24.00	27.20
B2011H-14P	26.00	29.20
B2011H-15P	28.00	31.20
B2011H-16P	30.00	33.20

CJTconn CHANGJIANG CONNECTORS CO.,LTD.			
Unit	Scale	Sheet	TITLE
mm	6:1	1 of 1	2.00mm PITCH HOUSING
DRWN	CHKD	APPR	
Chengbiao Ye	Diankui Wan	Jack Yin	DRAWING NO. B2011H-XP
General Tolerances		THIRD ANGLE PROJECTION	
A4	CHANGE THE DRAWING	2023.02.22	REV A4
A3	MODIFY DRAWING	2022.01.13	
A2	MODIFY DRAWING	2021.09.14	B2011H-XP
A1	ADD THE SIZE	2020.07.23	
A0	NEW RELEASE	2009.05.10	B2011H-XP
REV	DESCRIPTION	DATE	