


P.C.B YAYOUT
TOLERANCE:±0.05



Ordering Information:

B2011HB-XP - ***
1 2

1.Part NO.

2.Color:

(Blank): Black

WH: White

SPECIFICATIONS:

Current Rating: 2A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 20mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 800V AC/minute

Material: Nylon 66,UL94V-0

Ordering Information & Dimensions

Part NO.	Dimensions(mm)	
	A	B
B2011HB-2P	2.00	4.80
B2011HB-3P	4.00	6.80
B2011HB-4P	6.00	8.80
B2011HB-5P	8.00	10.80
B2011HB-6P	10.00	12.80
B2011HB-7P	12.00	14.80
B2011HB-8P	14.00	16.80
B2011HB-9P	16.00	18.80
B2011HB-10P	18.00	20.80
B2011HB-11P	20.00	22.80
B2011HB-12P	22.00	24.80
B2011HB-13P	24.00	26.80
B2011HB-14P	26.00	28.80
B2011HB-15P	28.00	30.80
B2011HB-16P	30.00	32.80
B2011HB-17P	32.00	34.80
B2011HB-18P	34.00	36.80
B2011HB-19P	36.00	38.80
B2011HB-20P	38.00	40.80

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

A0	NEW RELEASE	2023.03.20
REV	DESCRIPTION	DATE

Unit	Scale	Sheet
mm	6:1	1 of 1
DRAWN	CHK'D	APPR
Haisen Li	Diankui Wan	Jack Yin
General Tolerances		THIRD ANGLE PROJECTION
x.xx±0.25		
x.xx±0.20		
x.xxx±0.15		
ANGLES ±1°		

TITLE		
2.00mm PITCH HOUSING		
DRAWING NO.		REV
B2011HB-XP		A0