








Ordering Information:

- C3030WRA-F2-2xXP - ***
- 1.Part No.
- 2.Finish:
- (blank):Tin over Nickel
- G:Gold-flash
- G15:15µin (0.38µm) MIN.Select Gold
- 100µin (2.54µm) MIN.Select Tin
- G30:30µin (0.76µm) MIN.Select Gold
- 100µin (2.54µm) MIN.Select Tin



SPECIFICATIONS:

Current Rating: 12.5A AC,DC (AWG #18)

Voltage Rating: 600V AC,DC

Temperature Range: -40°C ~ +265°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute

Pin Material: Brass/Tin over Nickel

Material:Nylon 46,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2x1P	---	6.70	4.30	2x7P	18.00	24.70	22.30
2x2P	3.00	9.70	7.30	2x8P	21.00	27.70	25.30
2x3P	6.00	12.70	10.30	2x9P	24.00	30.70	28.30
2x4P	9.00	15.70	13.30	2x10P	27.00	33.70	31.30
2x5P	12.00	18.70	16.30	2x11P	30.00	36.70	34.30
2x6P	15.00	21.70	19.30	2x12P	33.00	39.70	37.30

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit			Scale	Sheet	TITLE	
mm			2:1	1 of 1	3.00mm PITCH	
DRWN		CHK'D	APPR	RIGHT-ANGLE DUAL ROW WAFER		
Xu Lei		Diankui Wan	Jack Yin			
General Tolerances			THIRD ANGLE PROJECTION		DRAWING NO.	
x.xx±0.25					C3030WRA-F2-2xXP	
x.xxx±0.20						
x.xxx±0.15						
ANGLES ±1°					REV	
					A2	

A2	CHANGE THE DRAWING	2022.01.17
A1	CHANGE THE Current Rating	2018.12.19
A0	NEW RELEASE	2012.12.06
REV	DESCRIPTION	DATE