









2x2P~2x6P

P.C.B LAYOUT
TOLERANCE:±0.05

2x7P~2x12P

Ordering Information:
C4140WR-2xXP - *** - ***
1 2 3

1.Part NO.

2.Material:

(Blank): Nylon 66,UL94V-0 (White)

46: Nylon 46,UL94V-0 (Ivory)

GWT: Nylon 66,UL94V-0 (Beige),
IEC 60335-1,5th Edition
Glow Wire Capable.

3.Finish:

(Blank): Tin over Nickel

G: Gold over Nickel

G15: Gold over Nickel (Au:15u",Mating Area)

G30: Gold over Nickel (Au:30u",Mating Area)

SPECIFICATIONS:

Current Rating: 9.5A AC,DC

Voltage Rating: 600V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 20mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute

Pin Material: Brass

Material: Nylon 66,UL94V-0

Ordering Information & Dimensions

Part NO.	Dimensions(mm)		
	A	B	C
C4140WR-2x2P	4.14	9.83	---
C4140WR-2x3P	8.28	13.97	---
C4140WR-2x4P	12.42	18.11	---
C4140WR-2x5P	16.56	22.25	---
C4140WR-2x6P	20.70	26.39	---
C4140WR-2x7P	24.84	30.56	16.56
C4140WR-2x8P	28.98	34.70	20.70
C4140WR-2x9P	33.12	38.84	16.56
C4140WR-2x10P	37.26	42.98	20.70
C4140WR-2x11P	41.40	47.12	16.56
C4140WR-2x12P	45.54	51.26	20.70

CJTconn CHANGJIANG CONNECTORS CO.,LTD.			
Unit	Scale	Sheet	TITLE 4.14mm PITCH RIGHT-ANGLE DIP WAFER
mm	1.5:1	1 of 1	
DRWN	CHKD	APPR	
Dengchun Yi	Djankui Wan	Jack Yin	
General Tolerances		THIRD ANGLE PROJECTION	DRAWING NO. C4140WR-2xXP
x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°			
			REV A3