


Ordering Information:

C4201HMB-2x2P-B - * - ***
1 2 3

1.Part No.

2.Material:

(Blank):Nylon 66 UL94V-2(Natural)

V0:Nylon 66 UL94V-0(White)

GWT:Nylon 66 UL94V-0(Beige), IEC 60335-1,5th
Edition Glow Wire Capable.

3.Color:

(Blank): see section 2 material

BK:Black

RD:Red

YL:Yellow

BL:Blue

GN:Green

SPECIFICATIONS:

Current Rating: 9A AC,DC

Voltage Rating: 600V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit		Scale		Sheet		TITLE	
mm		1.5:1		1 of 1		4.20mm Pitch Dual Row Housing With Panel Mount Ears	
DRWN		CHK'D		APPR			
Wenmin Luo		Diankui Wan		Jack Yin			
General Tolerances			THIRD ANGLE PROJECTION			DRAWING NO.	
x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°						C4201HMB-2x2P-B	
						REV A1	