











AFTER MATING



SECTION A-A



TYPE:

4	Shell	SUS304 T=0.30mm	Nickel 30u" Min Plating	1PCS
3	Shielding Plate	SUS301 T=0.15mm	---	1PCS
2	Contact	C18400-H T=0.12mm	Au 3u"Plated On Vontact Area GF Plated On Solder Area; Nickel 50u"Min Under Plating Over All.	2SET
1	Housing	PA9T/LCP UL94V-0	Black	1PCS
No.	Description	Material	Remarks	QTY


CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet	TITLE
mm	1:1	1 of 3	USB TYPE C FEMALE 16PIN Top-Mount TYPE SHELL L6.50mm
DRAWN	CHKD	APPR	
Haisen Li	Diankui Wan	Jack Yin	
General Tolerances		THIRD ANGLE PROJECTION	DRAWING NO.
x.xx±0.25 x.xx±0.20 x.xxx±0.15 ANGLES ±1°			CJ-CF055-16P

REV	DESCRIPTION	DATE
A0	NEW RELEASE	2023.05.16

REV
A0



RECOMMENDED PCB LAYOUT(TOP VIEW)
THICKNESS 0.60MM;DEFAULT TOLERANCE:±0.05

USB Type-C Pin Assignments

Pin Number	Signal Name	Pin Number	Signal Name
A1	GND	B12	GND
A2	---	B11	---
A3	---	B10	---
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	Dp1	B7	Dn2
A7	Dn1	B6	Dp2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	---	B3	---
A11	---	B2	---
A12	GND	B1	GND

SPECIFICATIONS:

- ELECTRICAL PERFORMANCE,
 - CURRENT RATING:5 AMPS. FOR TOTAL VBUS/GND PINS;
1.25AMPS FOR CC PIN,
0.25 AMPS. FOR ALL OTHER CONTACT.
 - VOLTAGE RATING:20V DC/AC (RMS. MAX)
 - CONTACT RESISTANCE: 40MΩ MAX INITIAL.
50MΩ MAX AFTER TEST
 - DIELECTRIC WITHSTANDING VOLTAGE: 100V AC
 - INSULATION RESISTANCE:100MΩ MIN
- MECHANICAL PERFORMANCE,
 - INSERTION FORCE: 5~20N.
 - EXTRACTION FORCE: 8~20N.
 - DURABILITY: 10000 CYCLES.
- ENVIRONMENTAL PERFORMANCE:
 - OPERATING TEMPERATURE: -25°C~+85°C.
- IR REFLOW:
 - THE PEAK TEMPERATURE ON THE BOARD SHALL BE MAINTAINED FOR 10 SECONDS AT 260°C.
- COMPLIANCE WITH ROHS & HF REQUIREMENTS.
- SALT SPRAY:48H

Ordering Information:

CJ-CF055 - 16P - *** - ** - ***
1 2 3 4

1.Part NO.

2.Material:

(Blank): PA9T,UL94V-0(Black)
LCP:LCP UL94V-0(Black)

3.Finish:

(Blank): Select Gold:3μin[0.076μm]Min.
Select Reflowed Gold Flash: 0.6μin[0.015μm] Min
Overall Nickel Underplate: 30μin[0.76μm Min.

G15: Select Gold:15μin[0.38μm]Min.

Select reflowed matte tin: 80μin[2.03μm] Min
Overall Nickel Underplate: 30μin[0.76μm Min.





G30: Select Gold:30μin[0.76μm]Min.

Select reflowed matte tin: 80μin[2.03μm] Min Overall
Nickel Underplate: 30μin[0.76μm Min.

4.Packing:

(Blank): Tape & Reel

CJTconn				CHANGJIANG CONNECTORS CO.,LTD.	
Unit	Scale	Sheet	TITLE		
mm	1:1	2 of 3			
DRAWN	CHKD	APPR			
Haisen Li	Diankui Wan	Jack Yin	USB TYPE C FEMALE 16PIN Top-Mount TYPE SHELL L6.50mm		
General Tolerances					
x.x±0.25 x.xx±0.20 x.xxx±0.15 ANGLES ±1°					REV A0
			DRAWING NO. CJ-CF055-16P		



	REEL	CARTON
CONNECTOR (PCS)	1200	12000

CJTconn CHANGJIANG CONNECTORS CO.,LTD.			TITLE
Unit	Scale	Sheet	USB TYPE C FEMALE 16PIN Top-Mount TYPE SHELL L6.50mm
mm	1:1	3 of 3	
DRAWN Haisen Li	CHKD Diankui Wan	APPR Jack Yin	
General Tolerances		THIRD ANGLE PROJECTION	DRAWING NO.
x.xx±0.25 x.xx±0.20 x.xxx±0.15 ANGLES ±1°			CJ-CF055-16P
A0	NEW RELEASE	2023.05.16	REV A0
REV	DESCRIPTION	DATE	