









SECTION A-A
SCALE 1:1

TYPE:

5	CAP	LCP UL94V-0	Black	1PCS
4	Shell	SUS304 T=0.30mm	Nickel 30u" Min Plating	1PCS
3	Shielding Plate	SUS301 T=0.15mm	---	1PCS
2	Contact	C18400-H T=0.12mm	Au 3u" Plated On Vcontact Area Tin 60u" Plated On Solder Area; Nickel 50u" Min Under Plating Over All.	2SET
1	Housing	LCP UL94V-0	Black	1PCS
No.	Description	Material	Remarks	QTY

CJTconn				CHANGJIANG CONNECTORS CO.,LTD.	
Unit	Scale	Sheet	TITLE		
mm	1:1	1 of 3	USB TYPE C FEMALE 16PIN VERTICAL TYPE SHELL H10.40mm		
DRAWN	CHK'D	APPR			
Haisen Li	Diankui Wan	Jack Yin			
General Tolerances		THIRD ANGLE PROJECTION	DRAWING NO.		REV A0
x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°					
			CJ-CF116-013-16P		





RECOMMEND P.C.B LAYOUT (COMPONENT SIDE)

TOLERANCE FOR PCB LAYOUT IS ± 0.05

SCALE:2:1

USB Type-C Pin Assignments

Pin Number	Signal Name	Pin Number	Signal Name
A1	GND	B12	GND
A2	---	B11	---
A3	---	B10	---
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	Dp1	B7	Dn2
A7	Dn1	B6	Dp2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	---	B3	---
A11	---	B2	---
A12	GND	B1	GND



AFTER MATING

REV	DESCRIPTION	DATE
A0	NEW RELEASE	2022.06.15

SPECIFICATIONS:

- ELECTRICAL PERFORMANCE
 - CURRENT RATING: 5 AMPS. FOR TOTAL VBUS/GND PINS;
1.25AMPS FOR CC PIN,
0.25 AMPS. FOR ALL OTHER CONTACT.
 - VOLTAGE RATING: 20V DC/AC (RMS. MAX)
 - CONTACT RESISTANCE: 40MΩ MAX INITIAL.
50MΩ MAX AFTER TEST
 - DIELECTRIC WITHSTANDING VOLTAGE: 100V AC
 - INSULATION RESISTANCE: 100MΩ MIN
- MECHANICAL PERFORMANCE
 - INSERTION FORCE: 5~20N.
 - EXTRACTION FORCE: 8~20N.
 - DURABILITY: 10000 CYCLES.
- ENVIRONMENTAL PERFORMANCE
 - OPERATING TEMPERATURE: -25°C~+85°C.
- IR REFLOW:
 - THE PEAK TEMPERATURE ON THE BOARD SHALL BE MAINTAINED FOR 10 SECONDS AT 260°C.
- COMPLIANCE WITH ROHS & HF REQUIREMENTS.
- SALT SPRAY: 48H

Ordering Information:

CJ-CF116-013 - 16P - *** - ***
1 2 3

1.Part NO.

2.Finish:

(Blank): Select Gold: 3μm[0.076μm]Min.

Select Reflowed matte tin: 60μm[1.50μm] Min

Overall Nickel Underplate: 50μm[1.25μm] Min.

G15: Select Gold: 15μm[0.38μm]Min.

Select reflowed matte tin: 80μm[2.03μm] Min

Overall Nickel Underplate: 30μm[0.76μm] Min.

G30: Select Gold: 30μm[0.76μm]Min.






Select reflowed matte tin: 80μm[2.03μm] Min Overall

Nickel Underplate: 30μm[0.76μm] Min.

3.Packing:

(Blank): Tape & Reel Cap

CJTconn				CHANGJIANG CONNECTORS CO.,LTD.	
Unit	Scale	Sheet	TITLE		
mm	1:1	2 of 3	USB TYPE C FEMALE 16PIN VERTICAL TYPE SHELL H10.40mm		
DRAWN	CHK'D	APPR			
Haisen Li	Diankui Wan	Jack Yin			
General Tolerances		THIRD ANGLE PROJECTION		DRAWING NO.	
x.xx±0.25 x.xx±0.20 x.xxx±0.15 ANGLES ±1°					
				REV A0	
				CJ-CF116-013-16P	



	REEL	CARTON
CONNECTOR (PCS)	450	4500

CJTconn CHANGJIANG CONNECTORS CO.,LTD.			
Unit	Scale	Sheet	TITLE
mm	1:1	3 of 3	USB TYPE C FEMALE 16PIN VERTICAL TYPE SHELL H9.30mm
DRAWN	CHK'D	APPR	
Haisen Li	Diankui Wan	Jack Yin	
General Tolerances		THIRD ANGLE PROJECTION	
x.x±0.25 x.xxx±0.20 x.xxx±0.15 ANGLES ±1°			
DRAWING NO.			REV
CJ-CF116-013-16P			A0