








TYPE:

4	Shell	SUS304 T=0.30mm	Nickel 30u" Min Plating	1PCS
3	Shielding Plate	SUS301 T=0.15mm	Nickel 30u" Min Plating	1PCS
2	Contact	C18400 T=0.12mm	Au 3u"Plated On Vontact Area GF Plated On Solder Area; Nickel 50u"Min Under Plating Over All.	2SET
1	Housing	PA9T UL94V-0	Black	1PCS
No.	Description	Material	Remarks	QTY

CJTconn CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet	TITLE
mm	1:1	1 of 3	USB4 TYPE C FEMALE 24PIN Top-Mount TYPE SHELL L8.17mm
DRAWN Haisen Li	CHK'D Diankui Wan	APPR Jack Yin	
General Tolerances		THIRD ANGLE PROJECTION	
x.xx±0.25 x.xx±0.20 x.xxx±0.15 ANGLES ±1°		DRAWING NO. CJ-CF224-010-24P	
A0	NEW RELEASE	2020.08.26	REV A0
REV	DESCRIPTION	DATE	



USB Type-C Pin Assignments

Pin Number	Signal Name	Pin Number	Signal Name
A1	GND	B12	GND
A2	TX1+	B11	TX1+
A3	TX1-	B10	TX1-
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	Dp1	B7	Dn2
A7	Dn1	B6	Dp2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	RX2-	B3	RX2-
A11	RX2+	B2	RX2+
A12	GND	B1	GND

SPECIFICATIONS:

- ELECTRICAL PERFORMANCE,
 - CURRENT RATING: 5 AMPS. FOR TOTAL VBUS/GND PINS;
1.25AMPS FOR CC PIN,
0.25 AMPS. FOR ALL OTHER CONTACT.
 - VOLTAGE RATING: 20 V DC/AC (RMS. MAX)
 - CONTACT RESISTANCE: 40m Ω MAX INITIAL.
50m Ω MAX AFTER TEST
 - DIELECTRIC WITHSTANDING VOLTAGE: 100V AC
 - INSULATION RESISTANCE: 100M Ω MIN
- MECHANICAL PERFORMANCE,
 - INSERTION FORCE: 5~20N.
 - EXTRACTION FORCE: 8~20N.
 - DURABILITY: 10000 CYCLES.
- ENVIRONMENTAL PERFORMANCE:
 - OPERATING TEMPERATURE: -25°C~+85°C.
- IR REFLOW:
 - THE PEAK TEMPERATURE ON THE BOARD SHALL BE MAINTAINED FOR 10 SECONDS AT 260°C.
- COMPLIANCE WITH ROHS & HF REQUIREMENTS.
- SALT SPRAY: 48H

Ordering Information:

CJ-CF224-010 - 24P - *** - ***
1 2 3

1.Part NO.

2.Finish:

(Blank): Select Gold: 3 μ m[0.076 μ m]Min.

Select Reflowed Gold Flash: 0.6 μ m[0.015 μ m] Min

Overall Nickel Underplate: 50 μ m[1.25 μ m] Min.

G15: Select Gold: 15 μ m[0.38 μ m]Min.

Select reflowed matte tin: 80 μ m[2.03 μ m] Min

Overall Nickel Underplate: 30 μ m[0.76 μ m] Min.

G30: Select Gold: 30 μ m[0.76 μ m]Min.


Select reflowed matte tin: 80 μ m[2.03 μ m] Min Overall

Nickel Underplate: 30 μ m[0.76 μ m] Min.



3.Packing:

(Blank): Tape & Reel

CJTconn CHANGJIANG CONNECTORS CO.,LTD.			
Unit	Scale	Sheet	TITLE USB4 TYPE C FEMALE 24PIN Top-Mount TYPE SHELL L8.17mm
mm	1:1	2 of 3	
DRAWN	CHK'D	APPR	
Haisen Li	Diankui Wan	Jack Yin	
General Tolerances		THIRD ANGLE PROJECTION	DRAWING NO.
x.x±0.25 x.xx±0.20 x.xxx±0.15 ANGLES ±1°			
		CJ-CF224-010-24P	
REV		A0	



SEE DETAIL X



PAPER BOARD

REEL AND TAPE

REEL AND TAPE

PAPER BOARD

FOLDER
PAPER BOARD

CARTON

	REEL	CARTON
CONNECTOR (PCS)	1100	11000

CJTconn CHANGJIANG CONNECTORS CO.,LTD.			
Unit	Scale	Sheet	TITLE USB4 TYPE C FEMALE 24PIN Top-Mount TYPE SHELL L8.17mm
mm	1:1	3 of 3	
DRAWN	CHK'D	APPR	
Haisen Li	Diankui Wan	Jack Yin	
General Tolerances		THIRD ANGLE PROJECTION	
x.x±0.25 x.xx±0.20 x.xxx±0.15 ANGLES ±1°			DRAWING NO.
			CJ-CF224-010-24P
			REV A0